

Republic of thePhilippines PARTIDO DEVELOPMENT ADMINISTRATION Created Under R.A. 7820

Tigaon, Camarines Sur

, 20		
7(1)	20	
	7()	

ITEM DESCRIPTION	QTY.	UNIT	UNIT	TOTA
Supply & delivery of logging turbidity meter portable microprocessor, battery Range: 0.00 to 50.00 FTU, 50 to 1000 FTU Resolution: 0.01 & 1 FTU Accuracy: (+/-) 0.5 FTU or (+/-) 5% of reading Calibration: 3 point (0, 10 & 500 FTU) Typical EMC Deviation: (+/-) 2% FS Light Source: Infra Red Light Source Life: Life of Instrument Light detector: Silicon Photo Cell Battery Type: 4 x 1.5V AA Alkaline	5	Units	ATOT Williams So the recommendation	
Battery Life: Approx. 60 hrs. use Auto-off: 5 minutes of non-use Compliant to ISO 7027 Provided as kit w/ rugged carrying case: - Sample curvettes (min. 2 pcs.)	participal in the second	Maca		
- Caps (min. 2 pcs) - Calibration solution (0 & 10 FTU) - Tissue for wiping curvettes	S S			

Sir/Madam: I have the honor to offer my prices for each of the above articles as indicated after each item hereon. Very truly yours